

# Ecoteller<sup>®</sup>

From the Pioneers of Low-Power ATMs

## World's Lowest Power- consuming ATM

### Eco-Friendly

- Operates from 5°C to 45°C
- Designed to operate without AC
- Affordable Solar Option

### Highly Secured

- Linux operating system
- Advanced security features

### Reliable and User-Friendly

- Designed with lesser moving parts
- Multilingual receipt printing without switch intervention



AN ISO 9001:2008 & 14001:2015 CERTIFIED COMPANY



**vortex**<sup>TM</sup>

Helping banks reach out

*The Ecoteller® ATM consumes very less power ensuring maximum availability in a wide range of environmental conditions - temperature and humidity. Ecoteller® ATMs can be viably run by greener power sources like solar power and thus could even operate at zero emissions.*

## TECHNICAL DATA

### ■ Installation Type

- Lobby, Cash Dispenser with front replenishment
- Onsite and offsite model

### ■ Processor

- Intel 1.6 GHz Atom processor
- 2GB RAM
- Primary HDD: 1 X 500 GB HDD

### ■ Currency Chest

- UL291-L1 certified safe
- Dual-combination electronic lock
- OTC Lock (Optional)
- Mechanical key lock (Optional)

### ■ Dispenser

- Friction pick technology
- Bunch presenter with a maximum capacity of 40 notes per transaction
- 2-cassette OR 4-cassette configuration
- Cassette capacity - 2500 pieces of fresh currency notes
- Convenience cassettes
- Secure Cassettes with lock and key or Tag (Optional)
- Purge bin

### ■ Card reader

- Dip card reader
- Motorized Card Reader (Optional)
- Anti-skimming (Optional)
- EMV Version 4.0

### ■ Finger Print reader

### ■ Customer Interface on ATM

- 10/15-inch LCD with vandal-proof screen
- Touch Screen (Optional)
- 8 FDKs
- EPP Keypad - PCI-certified
- Audio jack with speaker for voice guidance
- In-built portrait camera / optional cash slot camera
- Privacy filter
- Lead through indicator

### ■ Receipt Printer

- 40-column Graphic Thermal Receipt printer, with a roll paper diameter of 150mm

### ■ Journal Printer (Optional)

- 40-column Graphic Thermal printer to print audit trail as per Bank's requirement, with a roll paper diameter of 80mm

### ■ Digital Video Surveillance system (DVSS)

- DVSS Camera with 10-metre USB Interface cable
- Secondary HDD: 1 X 500 GB HDD (For video storage)
- DVSS Software

### ■ ATM Security

- PADSS3.2 certified
- Security suite for OS/ Application hardening
- Terminal Security Solutions (Optional)

### ■ ATM Software

- Linux Operation System
- Vortex Swave Terminal Application
- EMV Level 2
- Electronic Journal

### ■ Management software (Optional)

- Vortex Management Center - server application for EJ pulling / remote ATM administration / content download
- Vortex Management Agent

### ■ Network Connectivity

- Supports TCP / IP protocol
- Can connect through VSAT, LAN, Leased line, GSM

### ■ Operating temperature & Environment protection

- Temperature: 5°C to 45°C
- Humidity: 10% to 90% RH

### ■ Power

- Input : 230V AC, 50Hz
- ATM average power consumption - 70W

### ■ Weight

- 420kg (with UL 291-L1 safe)

### ■ Dimensions

- 530mm (W) x 1435mm (H) x 740mm (D)



### Vortex Engineering Private Limited

No 6B, 6th Floor, IIT Madras Research Park, No.1. Kanagam Road, Taramani, Chennai 600 113, Tamil Nadu, INDIA.

Phone: +91 44 66 33 9700. Mobile: +91 9500001142. Mail: info@vortexindia.co.in